



STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

POZNAŃ/Ławica
RNAV RWY 28
DEKUT 2B ELSUP 2B ERNOX 2B OBOKU 2B XERBI 2B XIDNA 2B

DEKUT 2B

PDG 7% REQUIRED DUE TO OPERATIONAL REASONS UNTIL PO843

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY - OVER	COURSE/TRACK °M (°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE	SPEED (kt)	NAV SPEC
001	CF	PO801	-	282 (287.5)	12.00	-	+5400 ft	-	RNAV 1
002	TF	PO841	-	011 (017.3)	5.50	-	+FL070	-	RNAV 1
003	TF	PO842	-	017 (022.6)	6.65	-	+FL100	-	RNAV 1
004	TF	PO843	-	017 (022.6)	24.88	-	+FL180	-	RNAV 1
005	TF	DEKUT	-	052 (058.5)	6.90	-	-	-	RNAV 1

ELSUP 2B

PDG 7% REQUIRED DUE TO OPERATIONAL REASONS UNTIL ELSUP

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY - OVER	COURSE/TRACK °M (°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE	SPEED (kt)	NAV SPEC
001	CF	PO801	-	282 (287.5)	12.00	-	+5400 ft	-	RNAV 1
002	TF	PO851	-	269 (275.2)	13.03	-	+FL080	-	RNAV 1
003	TF	PO852	-	269 (274.9)	4.03	-	+FL100	-	RNAV 1
004	TF	ELSUP	-	269 (274.8)	22.77	-	-	-	RNAV 1

ERNOX 2B

PDG 7% REQUIRED DUE TO OPERATIONAL REASONS UNTIL PO806

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY - OVER	COURSE/TRACK °M (°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE	SPEED (kt)	NAV SPEC
001	CF	PO801	-	282 (287.5)	12.00	-	+5400 ft	-240	RNAV 1
002	TF	PO802	-	191 (197.3)	5.50	-	-	-240	RNAV 1
003	TF	PO803	-	101 (107.3)	6.00	-	+FL100	-	RNAV 1
004	TF	PO804	-	101 (107.4)	6.00	-	-	-	RNAV 1
005	TF	PO806	-	192 (197.5)	12.00	-	+FL130	-	RNAV 1
006	TF	ERNOX	-	247 (253.3)	24.87	-	-	-	RNAV 1

OBOKU 2B

PDG 7% REQUIRED DUE TO OPERATIONAL REASONS UNTIL PO821

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY - OVER	COURSE/TRACK °M (°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE	SPEED (kt)	NAV SPEC
001	CF	PO801	-	282 (287.5)	12.00	-	+5400 ft	-240	RNAV 1
002	TF	PO802	-	191 (197.3)	5.50	-	-	-240	RNAV 1
003	TF	PO803	-	101 (107.3)	6.00	-	+FL100	-	RNAV 1
004	TF	PO804	-	101 (107.4)	6.00	-	-	-	RNAV 1
005	TF	PO821	-	101 (107.5)	6.00	-	-	-	RNAV 1
006	TF	TENVO	-	092 (097.9)	31.95	-	-	-	RNAV 1
007	TF	OBOKU	-	075 (081.5)	8.42	-	-	-	RNAV1

XERBI 2B

PDG 7% REQUIRED DUE TO OPERATIONAL REASONS UNTIL PO833

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY - OVER	COURSE/TRACK °M (°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE	SPEED (kt)	NAV SPEC
001	CF	PO801	-	282 (287.5)	12.00	-	+5400 ft	-	RNAV 1
002	TF	PO831	-	298 (303.9)	10.38	-	+FL080	-	RNAV 1
003	TF	PO832	-	298 (303.7)	4.35	-	+FL100	-	RNAV 1
004	TF	PO833	-	298 (303.7)	11.38	-	+FL150	-	RNAV 1
005	TF	XERBI	-	330 (335.8)	20.21	-	-	-	RNAV 1

XIDNA 2B

PDG 7% REQUIRED DUE TO OPERATIONAL REASONS UNTIL PO806

SEQUENCE NUMBER	PATH TERMINATOR	WAYPOINT IDENTIFIER	FLY - OVER	COURSE/TRACK °M (°T)	DISTANCE (NM)	TURN DIRECTION	ALTITUDE	SPEED (kt)	NAV SPEC
001	CF	PO801	-	282 (287.5)	12.00	-	+5400 ft	-240	RNAV 1
002	TF	PO802	-	191 (197.3)	5.50	-	-	-240	RNAV 1
003	TF	PO803	-	101 (107.3)	6.00	-	+FL100	-	RNAV 1
004	TF	PO804	-	101 (107.4)	6.00	-	-	-	RNAV 1
005	TF	PO806	-	192 (197.5)	12.00	-	+FL130	-	RNAV 1
006	TF	XIDNA	-	149 (155.1)	29.59	-	-	-	RNAV 1

WAYPOINT IDENTIFIER	COORDINATES	
DEKUT	53 06 58.0 N	017 02 07.0 E
ELSUP	52 32 24.0 N	015 24 41.0 E
ERNOX	52 01 36.0 N	016 01 14.0 E
OBOKU	52 15 08.0 N	018 00 00.0 E
PO801	52 29 05.0 N	016 29 38.7 E
PO802	52 23 50.3 N	016 26 58.6 E
PO803	52 22 03.3 N	016 36 19.5 E
PO804	52 20 15.6 N	016 45 39.5 E
PO806	52 08 49.7 N	016 39 48.1 E
PO821	52 18 27.1 N	016 54 58.9 E
PO831	52 34 51.2 N	016 15 31.7 E
PO832	52 37 15.9 N	016 09 35.5 E
PO833	52 43 33.0 N	015 54 00.5 E
PO841	52 34 19.6 N	016 32 19.4 E
PO842	52 40 27.4 N	016 36 30.8 E
PO843	53 03 22.4 N	016 52 21.7 E
PO851	52 30 14.0 N	016 08 24.5 E
PO852	52 30 34.6 N	016 01 50.5 E
TENVO	52 13 54.1 N	017 46 27.1 E
XERBI	53 01 56.0 N	015 40 16.0 E
XIDNA	51 42 00.0 N	016 59 51.0 E